



**Red-White Valve Corp.**

20600 Regency Lane, Lake Forest, CA 92630

**Tel:** 1 (800) 222-RWVC (7982)

**Fax:** 1 (949) 859-7200

**Email:** [info@rwvcusa.com](mailto:info@rwvcusa.com)

## Item # 5044F 1/4, 5044F - Brass Full Port Ball Valve

150# WSP / 600# WOG

Brass body

Full port

Adjustable packing

FNPT x FNPT

Threaded ends (ASME B1.20.1-NPT)

Blow-out proof stem

MSS-SP-110

550 psi for UL use (1 1/2" & 2")

CSA 1/2, 5 & 125 psi (1/2" - 2")

CSA 1/2 & 5 psi (2 1/2" & 3")

UL approved (1/4" - 2")

FM approved (1/2" - 2")

Meet BAA requirement



### [Specifications](#) | [Dimensions](#)

#### Specifications

<b>Type</b>	Ball Valve
<b>Connection Type</b>	FNPT x FNPT

<b>Seat Material</b>	PTFE
<b>Stem Material</b>	Brass
<b>Ball Material</b>	Brass / Cr plated
<b>Size</b>	1/4
<b>Material</b>	Brass
<b>Operating Temperature [Min]</b>	15 °F
<b>Operating Temperature [Max]</b>	160 °F
<b>Operating Pressure [Max]</b>	600 psi
<b>Cv Coefficient</b>	8
<b>Valve Operator</b>	Lever Handle
<b>Valve Operator Material</b>	Steel / Geomet® plated
<b>Weight</b>	0.340 lb

## Dimensions

<b>Length A</b>	1.73 in
<b>Height H</b>	1.55 in
<b>Length L</b>	3.15 in