



Red-White Valve Corp.

20600 Regency Lane, Lake Forest, CA 92630

Tel: 1 (800) 222-RWVC (7982)

Fax: 1 (949) 859-7200

Email: info@rwvcusa.com

Item # 5044F 1-1/2, 5044F - Brass Full Port Ball Valve

150# WSP / 600# WOG

Brass body

Full port

Adjustable packing

FNPT x FNPT

Threaded ends (ASME B1.20.1-NPT)

Blow-out proof stem

MSS-SP-110

550 psi for UL use (1 1/2" & 2")

CSA 1/2, 5 & 125 psi (1/2" - 2")

CSA 1/2 & 5 psi (2 1/2" & 3")

UL approved (1/4" - 2")

FM approved (1/2" - 2")

Meet BAA requirement



[Specifications](#) | [Dimensions](#)

Specifications

Type Ball Valve

Connection Type FNPT x FNPT

Seat Material	PTFE
Stem Material	Brass
Ball Material	Brass / Cr plated
Size	1-1/2
Material	Brass
Operating Temperature [Min]	15 °F
Operating Temperature [Max]	160 °F
Operating Pressure [Max]	600 psi
Cv Coefficient	130
Valve Operator	Lever Handle
Valve Operator Material	Steel / Geomet® plated
Weight	3.120 lb

Dimensions

Length A	3.90 in
Height H	3.28 in
Length L	5.57 in